

cat. no. 103.02

Glazing of partition panels

DOUBLE-SIDED ADDITIONAL GLAZING OF METAL PARTITION



It is inserted into the existing partition panels, thickness 60, 80, 100 and 120 mm.

The window consists of a reinforcing profile, covering frames and sheet glass, thickness 4 or 6 mm.

TECHNICAL DATA

Type

additional double-sided Pharma glazing

Panel thickness

100 mm

120 mm

60 mm

80 mm

atypical

For partitions with a thickness of more than 200 mm, consultation with production is required.

Structural opening dimensions

width	height
1000 mm	1200 mm
1000 mm	1500 mm
600 mm	1200 mm
600 mm	1500 mm
800 mm	1200 mm
800 mm	1500 mm

Maximum structural opening dimensions 1500x1800 mm! – Glazing must be fitted across the two panels. This is an atypical design, it is recommended to always consult the production department. Min. height 800 mm, max. dimension 1500 mm.

Glazing

laminated safety glass, thickness 6 mm

atypical

float glass, thickness 4 mm

Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass.

Float glass design only for glazing with sill 1100mm and above.

Version

with inner frame

atypical

Frame hue and material

metal sheet, hue RAL 9002

metal sheet, hue RAL 9016

Stainless steel AISI 304

Komaxit, hue RAL

Atypical design

Type design

Atypical design

Type design

0 - Unique specification out of offered versions

Atypical design

Q - atypical design that cannot be uniquely specified by a code

MORE INFORMATION, PHOTOS

