## Glazing of partition panels

# **GLAZING IN PLASTERBOARD PARTITIONS**







With the system of partition panels, a glazed window panel represents one of the basic elements to construct clean workplaces and areas with maximum safety, sterility, hygiene, easy maintenance and sanitation.

The system in question is the PHARMA glazing system, offering double-sided glazing where the glass pane is in plane with the surface of the panel. Its design makes it suitable especially for hospital environments, areas in pharmaceutical industry, electrical engineering industry, mechanical engineering industry, food industry, etc.

## TECHNICAL DATA

**Type** 

Panel thickness	
100 mm	
125 mm	
150 mm	
75 mm	

Structural opening dimensions		
width	height	
1000 mm	1200 mm	
1000 mm	1500 mm	
1200 mm	1200 mm	
1200 mm	1500 mm	
800 mm	1200 mm	
800 mm	1500 mm	
Maximum dimensions of naminal ananing	P is 1500v1500mm   Min, width 560 mm, may dimension 1500 mm, Min, height 900 mm, may	

Maximum dimensions of nominal opening AxB is 1500x1500mm! Min. width 560 mm, max. dimension 1500 mm. Min. height 800 mm, max. dimension 1500 mm.

### Glazing

laminated safety glass, thickness 6 mm

float glass, thickness 4 mm

atypical

Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass.

Float glass design only for glazing with sill 1100mm and above.

#### Frame hue and material

metal sheet, hue RAL 9002

metal sheet, hue RAL 9016

Stainless steel AISI 304 FIN 8

metal sheet, hue RAL

### Atypical design

#### Type design

Atypical design

Type design

0 - Unique specification out of offered versions

Atypical design

Q - atypical design that cannot be uniquely specified by a code

# MORE INFORMATION, PHOTOS

